# **AFCONA - 3236**

# **Chemical Composition**

Organically modified polyalkyl polysiloxane.

## **Product general description**

Additive designed as slip and leveling agent with good defoaming effect.

## **Product Properties:**

Most organically modified polysiloxanes will stabilized foam and this make them not suitable for foam sensitive systems like floor coatings and high build systems. AFCONA-3236 is an alkyl modified polysiloxane giving not only slip and leveling properties, but also acts as a good defoamer in most systems.

AFCONA-3236 mostly used in foam sensitive systems as listed below due to none foam stabilizing properties:

- 1) Solvent –less epoxies
- 2) High Solid or solvent-less Polyurethanes
- 3) Paints applied by Curtain coater
- 4) Paints applied by airless spray application
- 5) UV curing systems

AFCONA-3236 also acts as good defoamer and slip agent for baking paints, especially in coil coatings. It has high temperature resistance up to 280°C for 15 minutes.

In wood coatings, AFCONA – 3236 also very often is used due to the good defoaming and slip performance. AFCONA – 3236 is not recommended in high gloss clear coats due to it can cause slight in-can haziness.

### **Product Specification**

Non-volatile matter	≥96% (120°C,0.5h)
Density	0.94 - 0.96g/cm <sup>3</sup> (20°C)
The refractive index	1.437 – 1.447 (25°C)
Flash point	>100°C
Gardner color	Max.2

# Appearance Transparent to slightly yellowish liquid (25°C)

### Addition and dosage

0.05 - 0.50% on total formulation. In general under normal conditions, the dosage is 0.05 - 0.2% based on total formulation.

### **Incorporation**

AFCONA-3236 can be added at any stage of production process. However, high shear force is needed if added in letdown stage due to the defoaming property. For easier incorporation, dilute to 10% in any solvent/s..

### **Storage**

AFCONA-3236 should be stored in a cool dry place. When kept in an original unopened container, it will keep up to 5 years from the date of manufacture. The expiry date is indicated on the container.

### **Packaging**

25kg and 190kg non-returnable containers

AFCONA ADDITIVES Web Site : <u>www.afcona.com</u>

This information and all further technical advice are based on our present knowledge and experience. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used. We reserve the right to make any changes according to science and technological progress or further developments.